

Photon HRC Camera Core

Miniature, Light Weight 640 MWIR
Cooled Camera Core



CORE BY INDIGO



Photon HRC is one of the smallest high-resolution (640x512) MWIR cooled camera cores in the world. Based on our 15-micron pitch, high performance, low power, Indium Antimonide (InSb) focal plane array, the Photon HRC camera core consists of a detector/dewar/cooler assembly (DDCA), and the camera electronics.

Photon HRC's electronics includes two cards: the power/video board and the cooler controller board. The camera outputs NTSC video, 8-bit corrected video and 14-bit digital data. Communication is over a serial (RS-232 or RS-422) interface. An optional ethernet module supports IP video data capture and communication. Photon HRC's steady-state power consumption is less than 8 Watts.

At less than 1 pound, and with its low power claim, Photon HRC is the perfect high-performance, miniature camera for small space platforms.

Features
High performance thermal imaging for long ranges
Photon HRC fits into tight spaces for high performance imaging in a small package
< 1 pound 640 MWIR camera
Low power (less than 8 Watts) 640 MWIR camera
New low price point
Out-of-the-box operable OEM core that interfaces with: <ul style="list-style-type: none">• Photon 640 accessories• A version of Photon 640 SDK and GUI
Interface with COTS IR optics



Specifications

Description	Features
Spectral Band	3.4 – 5.1 μm
Detector Material	InSb
Array Format	640 x 512
Detector Size	15 μm
Readouts	ISCD403
Well Capacity	7 million electrons
Detector Cooling	Closed Cycle Stirling-Rotary
Cooldown Time	5 minutes at 22°C and under 10 minutes at 71°C
Camera Cooling	Free air convection
Optical Interface	Custom
f/number	f/4
A/D	10.5 MHz, 14 bit
Noise Equivalent Temperature Difference (NE Δ T)	< 25 mK (<20 mK typical)
Maximum Pixel Rate	10.5 MHz
Maximum Frame Rate – Full Frame	30 Hz – 640 x 512
Video	NTSC and parallel 14 bit digital
Integration Time Range	Variable
Electronic Zoom	2X
Power Consumption	< 8 Watts steady state
Weight	< 1 lb
Operating Temperature	-40°C to +55°C



SANTA BARBARA CVS World Headquarters

FLIR Systems, Inc.
70 Castilian Drive.
Goleta, CA 93117
USA
PH: +1 805.964.9797
FX: +1 805.685.2711

PORTLAND Corporate Headquarters

FLIR Systems, Inc.
27700 SW Parkway Avenue
Wilsonville, OR 97070
USA
PH: +1 877.773.3547
FX: +1 503.498.3153

EUROPE CVS Eurasian Headquarters

FLIR Systems CVS BV
Charles Petitweg 21
4847 NW Teteringen - Breda
The Netherlands
PH: +31 (0) 765 79 41 94
FX: +31 (0) 765 79 41 99

www.flir.com
www.corebyindigo.com

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited.
Specifications are subject to change without notice. ©2008 FLIR Systems, Inc. All rights reserved. Rev A 6/08

In accordance with Exemption title 22 CFR §125.4.b.13, information contained in this publication has been approved for public release by the Office of Freedom of Information and Security Review, case no. 08-S-2290.